



## Thermal Transfer Ribbon Technical Data Sheet

### SK42425 Premium Near Edge Wax/Resin

#### Product Description

Part of a complete line of superior-performing near edge product solutions, SK42425 is the best ribbon on the market for thermal transfer printers equipped with near edge or corner edge printheads. SK42425 is designed with DNP's specially formulated backcoat technology for printhead protection as well as DNP's exclusive anti-static properties for easy handling and extra printhead protection. This ribbon prints dark images at high speeds and low energy settings on a wide variety of label and tag stocks from paper to low-end synthetics.

#### Recommended Applications



ASSET TRACKING



BEVERAGES



CONDIMENTS



COSMETICS



FLEXIBLE PACKAGING



GENERAL



HEALTHCARE



HORTICULTURE



INVENTORY



LOGISTICS



MEATS & CHEESES



MEDICAL DEVICES



OUTDOOR



PARTS PACKAGING



PHARMACEUTICAL



PRODUCE



PRODUCT ID



RETAIL



SHELF



SHIPPING



SNACK FOODS

#### Recommended Substrates

Coated/uncoated papers and tags, gloss paper, polyethylene, polyolefin, Tyvek®, Tyvek Brillion®, Kimdura, Valeron®, Polyart®

#### Performance Characteristics

- Halogen-Free
- Prints excellent images on a wide variety of label and tag stocks
- Anti-static for easy handling and extended printhead life
- DNP's specially formulated backcoating for printhead protection
- Unbeatable Edge Definition™ for dark, dense images and improved scan rates

*The information on this data sheet was obtained in DNP IMS America laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.*

Visit us at [www.snkasia.com](http://www.snkasia.com)

S & K Asia Sdn. Bhd.

29, Jalan Nilam 1/9, Subang Hi-Tech Industrial Park,  
40000 Shah Alam, Selangor, Malaysia.

TEL: +6010.540.8909

FAX: +603.5638.8909

EMAIL: [sales@snkasia.com](mailto:sales@snkasia.com)





## Thermal Transfer Ribbon Technical Data Sheet

### SK42425 Premium Near Edge Wax/Resin

#### Ribbon Properties

Description	Result	Test Method
Ink	Wax/Resin	
Color	Black	Visual
Total Thickness	8.2 ± 0.5µ	Micrometer
Base Film Thickness	4.8 ± 0.4µ	Micrometer
Ink Thickness	1.4 ± 0.3µ	Micrometer
Ink Melting Point	84°C (183°F)	Differential Scanning Calorimeter

#### Durability of Printed Image

Label Stock: Coated Paper

Print Speed: 6 IPS

Description	Result	Test Method
Print Density	> 1.86	Densitometer
Smudge Resistance	A*	Colorfastness Tester - 100 Cycles @ 500 Grams with Cotton Cloth
Scratch Resistance	A*	Colorfastness Tester - 50 Cycles @ 200 Grams with Stainless Steel Pointed Tip

\*American National Standard Institute (ANSI) Grade Levels A, B, C, D, and F, where A is excellent, B is above average, C is average, D is below average, and F is poor.

#### Conversion Chart

Millimeters (mm) to Inches = mm ÷ 25.4	Inches to Millimeters (mm) = Inches ÷ 0.03937
Meters (m) to Feet (ft) = m ÷ 0.3048	Feet (ft) to Meters (m) = Feet ÷ 3.2808
C° to F° = (1.8 X C°) + 32 = F°	F° to C° = (F° ÷ 1.8) - 17.77
Thousand square inches (MSI) to m <sup>2</sup> = MSI X 0.645	MSI = m <sup>2</sup> ÷ 0.645

The information on this data sheet was obtained in DNP IMS America laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

Visit us at [www.snkasia.com](http://www.snkasia.com)

S & K Asia Sdn. Bhd.  
 29, Jalan Nilam 1/9, Subang Hi-Tech Industrial Park,  
 40000 Shah Alam, Selangor, Malaysia.  
 TEL: +6010.540.8909  
 FAX: +603.5638.8909  
 EMAIL: [sales@snkasia.com](mailto:sales@snkasia.com)

