

SK82824 High Durable Near Edge Resin

Product Description

SK82824 offers the very quality resin printing for near edge applications. SK82824 is extremely versatile on a wide variety of substrates and also prints at extremely high speeds for faster turnaround. It outperforms the competition in abrasion and solvent resistance, and contains DNP's specially formulated backcoat technology for printhead protection, as well as DNP's exclusive anti-static properties for easy handling and extra printhead protection. Like all DNP ribbons, SK82824 is the industry leader in edge definition for clean, extremely durable, and dense bar codes.

Recommended Applications



Food & Beverage



Chemicals



Electronics



Health & Beauty



Outdoor

Recommended Substrates

Economy Synthetics

Synthetic paper
Polyethylene
Polyolefin
Polyester
Polypropylene
Valeron®
Kimdura®
Polyart®
PVC cards
Vinyl

Specialty Materials



Pharmaceutical



Automotive

Performance Characteristics

- ▶ Excellent print quality at high speeds
- ▶ Increased durability across a wide range of resin applications
- ▶ Extensive label adaptability for expanded application options
- ▶ Unbeatable edge definition for dark, dense images and improved scan rates
- ▶ DNP's specially formulated backcoating for printhead protection
- ▶ Anti-static for easy handling and extended printhead life



for more info!

S & K ASIA SDN. BHD.

29 Jalan Nilam 1/9,
Subang Hi-Tech Industrial Park
40000 Shah Alam, Selangor, Malaysia.
TEL: +6010.540.8909 FAX: +603.5638.8909
EMAIL: sales@snkasia.com / info@snkasia.com

S&K Global Customers
Malaysia, Singapore, Korea,
Indonesia, Philippines,
Vietnam, Thailand, India,
Middle East

SK82824 High Durable Near Edge Resin

Ribbon Properties

Description	Result	Test Method
Ink	Resin	
Color	Black	Visual
Total Thickness	5.8 ± 0.8μ	Weight
Base Film Thickness	4.5 ± 0.4μ	Weight

Durability of Printed Image

Label Stock: Top-coated Polyester

Print Speed: 6 IPS

Description	Result	Test Method
Print Density	> 1.80	Densitometer
Smudge Resistance	A*	Colorfastness Tester - 100 Cycles @ 500 Grams with Cotton Cloth
Scratch Resistance	A*	Colorfastness Tester - 50 Cycles @ 200 Grams with Stainless Steel Pointed Tip

*American National Standard Institute (ANSI) Grade Levels A, B, C, D, and F, where A is excellent, B is above average, C is average, D is below average, and F is poor.

Conversion Chart

Millimeters (mm) to Inches = mm ÷ 25.4	Inches to Millimeters (mm) = Inches ÷ 0.03937
Meters (m) to Feet (ft) = m ÷ 0.3048	Feet (ft) to Meters (m) = Feet ÷ 3.2808
C° to F° = (1.8 X C°) + 32 = F°	F° to C° = (F° ÷ 1.8) - 17.77
Thousand square inches (MSI) to m ² = MSI X 0.645	MSI = m ² ÷ 0.645



The information on this data sheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

S & K ASIA SDN. BHD.

29 Jalan Nilam 1/9,
Subang Hi-Tech Industrial Park
40000 Shah Alam, Selangor, Malaysia.
TEL: +6010.540.8909 FAX: +603.5638.8909
EMAIL: sales@snkasia.com / info@snkasia.com

S&K Global Customers
Malaysia, Singapore, Korea,
Indonesia, Philippines,
Vietnam, Thailand, India,
Middle East