### SUPERIOR DURABILITY SOLVENT INK





SOLVENT BASED / NON-POROUS



**QUICK - DRY** 



SUPER FAST PRINTING



600DPI RESOLUTION

### EZINK

THETA

EZ INK Theta cartridge is non-porous ink formulated to withstand extreme applications on smooth & glossy surfaces such as PP, PET, gloss coated surface and many more. EZ INK Theta has the market highest scratch & smudge resistance. It has waterproof and oil resistance properties increase the durability drastically.

## EZINK

# THETA

#### **Superior Printing on Non-Porous Surfaces**

EZ INK Theta is the market highest smudge & scratch resistance ink, capable to print on a wide range of non-porous materials and highly waterproof. The printing will be ultra durable to withstand any extreme environment.

#### **Quick-dry Ink Formulation**

EZ INK Theta has a quick-dry ink formulation which makes the printing stick to the substrates almost instantly.

#### High Speed, High Resolution Printing

EZ INK Theta capable of printing high resolution 600Dpi images even at high speed which results in dark and highly precise printing.

#### Capable of 2D Barcode & QR code Printing

EZ INK Theta cartridge is designed with dual nozzle head which allows the printing to be solid and barcode friendly for any tracking and handling requirements.





#### **Specifications**

Cartridge HP 45Si Genuine Cartridge

Ink type Solvent-Based

Ink volume 42ml

Print Height 12.7mm

Print Distance 2-5mm

De-cap Time 1 hour

Storage life 9 months

Storage condition 15°C ~ 35°C (Room Temp)

#### **Handling Instruction**

- 1. Always keep the cover on the cartridge when not in use.
- 2. Clean the head first after opening the cover.
- 3. Avoid inserting / removing the cartridge during "Printing" mode.
- 4. Insert the cartridge carefully into the printer printhead assembly.

#### Compatible Substrates

- 1. Craft Paper
- 2. Carton Box
- 3. Wood
- 4. Coated surface
- 5. Plastic (PP, PET..)
- Bottle
- 7. Metal, Aluminum
- 8. PVC
- 9. Film
- 10. Glass

<sup>\*</sup>Product of S&K Asia

<sup>\*</sup>Specifications and information in this technical datasheet may change without prior notice.

<sup>\*</sup>Please visit www.snkasia.com to get the latest datasheet for this product.