




SK1881

SK SERIES WAX



Technical Data Sheet

Product Description

SK1881 is specially formulated to perform across a wide range of energy and speed settings, providing a cost-effective solution for everyday thermal transfer printing. It incorporates advanced anti-static technology and a durable backcoat layer to protect the printhead and ensure stable printing performance. The wax-based ink formulation produces dark images and sharp, clear barcodes for reliable scanning.

Applications



Food & Beverage



Inventory & Logistics



Retail

Recommended Substrates

Paper

- ✓ Coated paper
- ✓ Coated Tag
- ✓ Uncoated paper
- ✓ Uncoated Tag

Performance Characteristics

- ✓ Suitable for a wide range of applications
- ✓ Scratch resistance
- ✓ Smudge resistance
- ✓ Capable of print speeds up to 12 IPS
- ✓ Dark glossy printed image
- ✓ Halogen-free

More Info



RIBBON PROPERTIES

Description	Result	Test Method
Ink	Wax	
Color	Black	Visual
Total Thickness	7.8 ± 0.6μ	Micrometer
Base Film Thickness	4.8 ± 0.3μ	Micrometer

DURABILITY OF PRINTED IMAGE

Description	Result	Test Method
Print Density	> 1.80	Densitometer
Smudge Resistance	A*	Colorfastness Tester - 50 Cycles @ 500 Grams with Cotton Cloth
Scratch Resistance	A*	Colorfastness Tester - 20 Cycles @ 200 Grams with Stainless Steel Pointed Tip

Label Stock: Coated Paper

Print Speed: 6 IPS

*American National Standard Institute (ANSI) Grade Levels A, B, C, D, and F, where A is excellent, B is above average, C is average, D is below average, and F is poor.



The information on this data sheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

S & K ASIA SDN. BHD.

17, Jalan TP 7/7, Section 26, SIME UEP Industrial Park, 40400 Shah Alam, Selangor, Malaysia.

